

GV642D65

gorenje *Life Simplified*

G400 Integrated dishwasher, 60 cm



EuropeanQuality



TotalDry



ConstaDrive
Motor



Fast 1h



AutoProgramme



ExtraHygiene



SmartControl



14 place settings




MultiClack




UltraClean
cutlery basket



Total AquaStop



Effortless
GlideGuides



GlassProgramme



15min
SpeedWash



Dishwasher
UltraClean



SelfCleaning
filter



SelfCleaning
programme

General information

Product group:	Dishwasher	Energy efficiency class:	D
Noise class:	C	Basket helper colour:	Orange
Spray arm material:	Plastic		

Efficiency

Cleaning performance:	A	Drying performance:	A
Drive:	Asynchronous motor	Water consumption per cycle for the Eco program:	9.701 l
Max. temperature of inflow water:	70 °C	Energy consumption per cycle for the Eco program 40-60 °C:	0.831 kWh
Energy consumption per 100 cycles:	83 kWh	Consumption in standby mode:	0.49 W
Start delay (W):	3.99		

Control

Possible to control via Wi-Fi:	No	Control:	TouchControl
Wash end indicator:	Light - sound signal	Start delay:	0-24 hours
Function 3 in 1:	Yes		

Programmes

Dishwashing programs:	Intensive programme, Automatic programme, Eco programme, Programme Hygiene, Crystal glasses, 1h wash	Ability to create own programmes:	Memory programme
Main wash temperature (°C):	40/45/50/55/60/65/70	Duration of Eco programme:	190 min

Features

Number of place settings:	14 pcs	Upper basket system:	Click-Clack system
Sliding door:	No	Interior light:	No
Status LedLight:	No	Additional possibilities:	SpeedWash function, TotalDry, automatic door opening, Selfcleaning programme
Ioniser:	No	Sensors:	Water level sensor, Clear water sensor
AutoDose System:	No		

Equipment

Number of baskets:	2	Upper basket:	Wide mesh base, Foldable left CupHolder, Foldable/dividable left CupHolder, Fixed pin rows, Fixed glass support, Wide knife stand, 2 cup holders
Lower basket:	Wide mesh base, Foldable/dividable rear pin row, Cutlery basket	Top tray:	Without top tray

Safety

Overflow protection:	Total AquaStop	Service diagnostic indicator:	Yes
Tub material:	Stainless steel		

Technical data

Noise level (max) dB(A):	47	Height setting:	74 mm
Width of the product:	598 mm	Height of the product:	816 mm
Depth of the product:	555 mm	Width of niche size for installation min.:	600 mm
Height of niche size for installation min.:	820 mm	Depth of niche size for installation min.:	555 mm
Width of the packed product:	640 mm	Height of the packed product:	880 mm
Depth of the packed product:	665 mm	Gross weight:	31.1 kg
Net weight:	29.3 kg	Voltage:	220-240 V
Product code:	745176	EAN code:	3838782945304
EPREL number:	2104967		



Fixed door height 21, 645-729 (mm), Sliding door 688-768 (mm)

Niche height (mm)		820	830	840	850	860	870	880	890
60	760								
70	750	760							
80	740	750	760						
90	730	740	750	760					
100	720	730	740	750	760				
110	710	720	730	740	750	760			
120	700	710	720	730	740	750	760		
130	690	700	710	720	730	740	750	760	
140	680	690	700	710	720	730	740	750	
150	670	680	690	700	710	720	730	740	
160	660	670	680	690	700	710	720	730	
170	650	660	670	680	690	700	710	720	
180	640	650	660	670	680	690	700	710	
190	640	650	660	670	680	690	700		
200		640	650	660	670	680	690		
210			640	650	660	670	680	690	
220				640	650	660	670	680	690
230					640	650	660	670	680
240						640	650	660	670
250							640	650	660
260								640	650

730 Sliding door
700 Sliding door or fixed door
670 Fixed door

