

GV16D5

gorenje *Life Simplified*

G400 Integrated dishwasher, 60 cm



EuropeanQuality



TotalDry



ConstaDrive Motor



Fast 1h



FlexUse




AutoProgramme



ExtraHygiene



SmartControl




16 place settings



MultiClack



Total AquaStop



Effortless
GlideGuides



GlassProgramme



Adjustable
baskets



15min
SpeedWash



Dishwasher
UltraClean



SelfCleaning
filter



SelfCleaning
programme



ThirdRack

General information

Product group:	Dishwasher	Energy efficiency class:	D
Noise class:	B	Basket helper colour:	Orange
Spray arm material:	Plastic		

Efficiency

Cleaning performance:	A	Drying performance:	A
Drive:	Asynchronous motor	Water consumption per cycle for the Eco program:	10.9 l
Max. temperature of inflow water:	70 °C	Energy consumption per cycle for the Eco program 40-60 °C:	0.85 kWh
Energy consumption per 100 cycles:	85 kWh	Consumption in standby mode:	0.49 W
Start delay (W):	3.99		

Control

Possible to control via Wi-Fi:	No	Control:	TouchControl
Wash end indicator:	Light - sound signal	Start delay:	0-24 hours
Function 3 in 1:	Yes		

Programmes

Dishwashing programs:	Intensive programme, Automatic programme, Eco programme, Programme Hygiene, Crystal glasses, 1h wash	Ability to create own programmes:	Memory programme
Main wash temperature (°C):	40/45/50/55/60/65/70	Duration of Eco programme:	175 min

Features

Number of place settings:	16 pcs	Upper basket system:	Click-Clack system
Sliding door:	No	Interior light:	No
Status LedLight:	No	Additional possibilities:	SpeedWash function, TotalDry, automatic door opening, Selfcleaning programme
Ioniser:	No	Sensors:	Water level sensor, Clear water sensor
AutoDose System:	No		

Equipment

Number of baskets:	3	Upper basket:	3 cup holders, Wide knife stand, Fixed glass support, Fixed pin rows, Foldable/dividable left CupHolder, Foldable right CupHolder, Foldable left CupHolder, Wide mesh base
Lower basket:	Wide mesh base, Foldable/dividable rear pin row	Top tray:	Dividable and removable, With telescopic rails, Handle, Plastic handle, Removable, No logotype

Safety

Overflow protection:	Total AquaStop	Service diagnostic indicator:	Yes
Tub material:	Stainless steel		

Technical data


Noise level (max) dB(A):	44	Height setting:	74 mm
Width of the product:	598 mm	Height of the product:	816 mm
Depth of the product:	555 mm	Width of niche size for installation min.:	600 mm
Height of niche size for installation min.:	820 mm	Depth of niche size for installation min.:	555 mm
Width of the packed product:	640 mm	Height of the packed product:	880 mm
Depth of the packed product:	665 mm	Gross weight:	31.5 kg
Net weight:	29.7 kg	Voltage:	220-240 V
Product code:	745178	EAN code:	3838782946349
EPREL number:	2104968		



Fixed door height 2L 645-729 (mm), Sliding door 688-768 (mm)

Niche height (mm)	820	830	840	850	860	870	880	890
60	760							
70	750	760						
80	740	750	760					
90	730	740	750	760				
100	720	730	740	750	760			
110	710	720	730	740	750	760		
120	700	710	720	730	740	750	760	
130	690	700	710	720	730	740	750	760
140	680	690	700	710	720	730	740	750
150	670	680	690	700	710	720	730	740
160	660	670	680	690	700	710	720	730
170	650	660	670	680	690	700	710	720
180	640	650	660	670	680	690	700	710
190	640	650	660	670	680	690	700	
200		640	650	660	670	680	690	
210			640	650	660	670	680	
220				640	650	660	670	
230					640	650	660	
240						640	650	
250							640	
260								640

730 Sliding door
700 Sliding door or fixed door
670 Fixed door



Special installation can be used with higher doors